

M23圆形信号连接器

现场接线

6针

3+PE+4针

3+PE+5针



插针 延长式连接器

| 1 | 型号 | No. | M23-6MS.P-DL | M23-8MS.P-DL | M23-9MS.P-DL | | | | | | | | | | | | | |
|--------------|---|--|---|--|--|------|-----|--------------|-------------------------|----------|------------------------|----------|--------------|------------------------|----------|------------------------|----------|--|
| | 极数 | | 6p(6xφ2) | 8p(4xφ2+4xφ1) | 9p(4xφ2+5xφ1) | | | | | | | | | | | | | |
| | 电缆出线直径 | | 7-17mm | 7-17mm | 7-17mm | | | | | | | | | | | | | |
| | 针脚排序 | |  |  |  | | | | | | | | | | | | | |
| 2 | 技术参数 | | 6p(6xφ2) | 8p(4xφ2+4xφ1) | 9p(4xφ2+5xφ1) | | | | | | | | | | | | | |
| | 额定电压 | | 630 V (AC/DC) / 250 V (AC/DC) | 630 V (AC/DC) / 250 V (AC/DC) | 630 V (AC/DC) / 250 V (AC/DC) | | | | | | | | | | | | | |
| | 额定电流 | | 28A | 28A/8A | 28A/8A | | | | | | | | | | | | | |
| | 防护等级 | | IP67-插孔插针配合拧紧 | IP67-插孔插针配合拧紧 | IP67-插孔插针配合拧紧 | | | | | | | | | | | | | |
| | 温度范围 | | -20...+130℃ | -20...+130℃ | -20...+130℃ | | | | | | | | | | | | | |
| | 测试电压(两插针之间) | | 4000V | 4000V/2500V | 4000V/2500V | | | | | | | | | | | | | |
| | 外壳材料 | | 锌合金压铸件 黄铜, 镀镍 | 锌合金压铸件 黄铜, 镀镍 | 锌合金压铸件 黄铜, 镀镍 | | | | | | | | | | | | | |
| | 绝缘内嵌体材料 | | PA66/PBT,UL 94/V0 | PA66/PBT,UL 94/V0 | PA66/PBT,UL 94/V0 | | | | | | | | | | | | | |
| | 接触件 (插针/插孔) | |  <p>∅ 1 mm</p> <p>∅ 2 mm</p> | <table border="1"> <thead> <tr> <th>类型</th> <th>压线范围</th> <th>订货号</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插针 ∅ 1 mm</td> <td>0.14-0.5mm²</td> <td>EDF1-0.5</td> </tr> <tr> <td>0.5-1.0mm²</td> <td>EDF1-1.0</td> </tr> <tr> <td rowspan="2">插针 ∅ 2 mm</td> <td>1.0-2.5mm²</td> <td>EDF2-2.5</td> </tr> <tr> <td>2.5-4.0mm²</td> <td>EDF2-4.0</td> </tr> </tbody> </table> | 类型 | 压线范围 | 订货号 | 插针 ∅ 1 mm | 0.14-0.5mm ² | EDF1-0.5 | 0.5-1.0mm ² | EDF1-1.0 | 插针 ∅ 2 mm | 1.0-2.5mm ² | EDF2-2.5 | 2.5-4.0mm ² | EDF2-4.0 | |
| 类型 | 压线范围 | 订货号 | | | | | | | | | | | | | | | | |
| 插针 ∅ 1 mm | 0.14-0.5mm ² | EDF1-0.5 | | | | | | | | | | | | | | | | |
| | 0.5-1.0mm ² | EDF1-1.0 | | | | | | | | | | | | | | | | |
| 插针 ∅ 2 mm | 1.0-2.5mm ² | EDF2-2.5 | | | | | | | | | | | | | | | | |
| | 2.5-4.0mm ² | EDF2-4.0 | | | | | | | | | | | | | | | | |
| 订货号 | | | | | | | | | | | | | | | | | | |
| | 订货范例 | <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; width: 100px; height: 20px; background-color: #ccc;"></div> <div style="border: 1px solid black; width: 100px; height: 20px; background-color: #ccc;"></div> <div style="border: 1px solid black; width: 100px; height: 20px; background-color: #ccc;"></div> </div> | | | | | | | | | | | | | | | | |
| | | 1 | 2 | 3 | | | | | | | | | | | | | | |
| | | 连接器类型 | 电缆线号 | 电缆长度 | | | | | | | | | | | | | | |
| | 订货型号的第二部分和第三部分可根据线号和长度不同自行修改, 电缆长度单位: M (米) | | | | | | | | | | | | | | | | | |